TD4C Portable Low Speed Centrifuge (Max speed: 4000rpm .Max volume:8x20ml)



Features

1. Widely used in laboratory, hospital and etc...
2. Brushless motor for model TD4C, free maintenance, no powder pollution, quick in speed up and down.
3. Range of speed from 0 to 4000rpm, smooth in operation, low noise and small vibration.
4. Micro computer control system, digital display the RCF, time and speed.
5. Electric cover lock, compact design, super speed and imbalance protection.
6. With over speed and imbalance protection.

TD4C Technical Parameter:

Max. Speed	4000rpm
Max. RCF	1880×g
Max. Capacity	8×20ml
Time Range	0~99min
RPM/RCF Convert	Yes
Noise (dB)	≤ 55
Temperature	Normal
Acc/Dec	10 Kinds
Speed Accuracy	±20r/min
Temperature Accuracy	/
Voltage(V/Hz)	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	310×270×220mm
Net Weight(Kg)	7.5KG
Certificates	CE,ISO & Calibration report are available

Matched Rotors for TD4C

Order No.	Rotor Type	Max Speed (rpm)	Max Volume (ml)	Max RCF(g)
4C-1	Angle Rotor	4000	8×15ml/20ml	1800
4C-2	Angle Rotor	4000	6×10ml/15ml/20ml	1880
4C-3	Angle Rotor	4000	12×5ml	1540
4C-4	Angle Rotor	4000	12×7ml	1540
4C-5	Angle Rotor	4000	12×10ml	1800
4C-6	Angle Rotor	4000	8x10ml vacuum tube	1800
			8x5ml vacuum tube adapter	1800
			8x7ml vacuum tube adapter	1800