

TD4A Low Speed Centrifuge



Features

1. TD4A centrifuge is of microprocessor control, less noisily, it is widely used to qualitative analysis of blood serum, plasma and urea in the fields of hospital, blood center, laboratory and biochemistry.
2. Brushless motor, free maintenance, no powder pollution, quick in speed up and down.
3. The flexible axle driven system which drive the rotor directly, smooth in operation and small vibration.
4. There are many rotors for your choice, suitable for different specifications meet customers' different requirements of separation.
5. Micro computer control system, LCD display the RCF, time and speed.
6. Electric lid lock, compact design, super speed and imbalance protection.

TD4A Technical Parameter:

Max. Speed	4000rpm
Max. RCF	2470×g
Max. Capacity	24×10ml
Time Range	0~99min
RPM/RCF Convert	Yes
Noise (dB)	≤ 55
Temperature	Normal
Acc/Dec	10 Kinds
Speed Accuracy	± 20r/min
Temperature Accuracy	/
Voltage(V/Hz)	AC 220V/110V 50HZ/60HZ
Size (W x D x Hmm)	485×320×255mm
Net Weight(Kg)	18KG
Certificates	CE,ISO & Calibration report are available

Matched Rotors for TD4A

Order No.	Rotor No.	Max Speed (rpm)	Max Volume (ml)	Max.RCF (×g)
N031605	Angle Rotor	4000	30×7/5ml	2250
N031604	Angle Rotor	4000	18×10ml	2250
N031607	Angle Rotor	4000	24×10/7/5ml	2200
N031602	Angle Rotor	4000	12×15/10/7/5ml	2150
N032667	Angle Rotor	4000	8×7/5ml	1800
N031606	Angle Rotor	4000	6×50ml	2100
N032665	Swing Rotor	4000	6×10ml	2390